



PAINTING FLEXCLAD™

FlexClad™ is a pre-fabricated, self-adhering, sheet-type waterproofing protective membrane designed to specifically protect ductwork and piping from the elements. FlexClad is designed to be left exposed to these elements indefinitely. Use for exterior, interior, sub-grade or in direct burial applications.

Good installation practices are critical to the performance of FlexClad. In general, MFM Building Products recommends installing FlexClad in fair weather conditions at temperatures above 40°F (4°C). Warmer temperatures increase the adhesion of the rubberized asphalt adhesive used in FlexClad.

When painting FlexClad, please follow the recommendations below:

- FlexClad, in all finishes (Aluminum, White, Almond and Granite Gray), can be painted with traditional exterior grade paints or may be coated with liquid roof coatings
- Test a small sample of FlexClad that is to be painted or coated to ensure that the selected paint or coating will properly adhere
- MFM recommends that the outer surface of the FlexClad be cleaned before painting or coating to remove any oils, asphalts, dust or dirt that may interfere with adhesion
- FlexClad is easily cleaned with acetone, denatured alcohol or similar non-oily solvent – wipe the outer surface with solvent and let dry before painting or coating
- For extremely dirty surfaces, first power wash the surface of FlexClad and then wipe the surface with a solvent
- FlexClad has a 10-Year Limited Warranty that applies only to the factory surface of the material and does not cover any paint or coating applied after installation

If you have any questions concerning the painting of FlexClad™, please contact MFM Technical Services at 800-882-7663 or 740-622-2645.

*Acetone is a flammable petroleum solvent and should be used with caution. Do not smoke in the presence of acetone or acetone fumes.